ROCHESTER STANDARD ADVANTAGE RANCH SPECIFICATIONS

House Floor Width & Roof Standards Floor width 26' wide Floor crawl space mode (basement prep available) Roof truss 6/12 24" oc, 16" oc available Roof eave and rake 10" Roof sheeting 7/16" Roof sub fascia 2x6 Roof attic access Ceiling drywall 5/8" Structural Standards Floor joist 2 x 10 16" oc #2 SPF or better Floor deck 3/4" Tongue & Groove, Ring Shank Nails, Handifoam Floor deck Cut back at mate line Floor band joist doubled sidewall, mate line Ceiling 8' height through out Walls exterior 2x6 16" oc, double top plate, 1/2" drywall Walls interior 2x4 24" oc ½" drywall Walls mate line 2x3 16" oc 1/2" drywall Walls exterior sheeted W/7/16" osb side, end and mateline **Heating Standards** Heat registers and boots Main Duct and furnace not provided as std. **Plumbing Standards** 1/2" PEX supply lines stubbed through floor per code Air Hammer Arresters install Washer, DW, if applicable PVC drain lines stubbed through floor Shut offs all exposed supply lines Delta single lever faucets, vanity, tubs- lifetime warranty Delta gooseneck kitchen faucet- lifetime warranty Stainless steel double bowl kitchen sink Gerber elongated commode and tank China lavs with overflows Fiberglass tub & shower/enclosures, per print All network of plumbing not included under floor **Electrical Standards** 200-amp Siemen service panel 40/40 Copper romex 14-2 wire all general circuits Copper romex wire other circuits sized accordingly Ground fault protection per code Arc fault protection all bedrooms Prepped for gas dryer per plan 110V for gas range per plan Smoke and carbon monoxide detectors per code 3-way switches per plan Kichler ceiling lights, double bulb, all bedrooms and living room LED recessed flush mount canister lights in kitchen Kichler LED light fixture in utility, hall, per print Kichler coach light by all exterior doors Kichler pendant lights over mirror all baths Broan light vent combination all baths Microwave prep standard over future range location Attic light Door Chime front door Exterior GFCI recept front and rear, per code Tamper resistant recepts All UTL circuits GFCI, all KIT circuits ARC fault AFCI, DW GFCI protected 10ft. Thermostat Wire coiled under floor through wall

Furnace prep per print- Finished closet w/ switched light, dedicated/switched 110 metal box W/H prep per print- Finished closet w/ switched light, dedicated 220 metal box

U: Lit Room/Standards Revised 1/31/2024

Accepted By:

Exterior Finish, Window, Door & Insulation Standards

Tyvek House wrap around entire house, gables included Ice dam protection eaves R-21 paperback batt insulation all exterior walls R38 blown attic insulation Vinyl 4x4 siding, prepped for sill plate fastening Vented vinyl soffit Aluminum fascia Owens Corning TruDefinition Duration shingles-limited lifetime warranty Silverline single hung windows (see options) Grids between glass Vinyl casement window over kitchen sink -per plan Tip out sash Low E2 Argon filled glass 15" raised panel shutters front of home only Thermatru Fiberglass front door peep hole and knocker 3'0" X 6'8" with lever action Schlage lockset Thermatru Steel rear door 20-minute fire rated 2'8" X 6'8" with lever action Schlage lockset, dead bolts keyed alike Caulking under all exterior walls Cabinet Standards Merillat Spring Valley Maple stained, recessed panel per plan Soft close doors & drawers, plywood construction full extension drawer box 30" Overhead wall cabinets, crown molding over all wall cabinets Lazy Susan in corner per plan Raised angle wall cabinet in corner per plan Raised Pantry Cabinet per plan Bank of drawers in base cabinets - bathrooms Laminate counters with rolled edge and Post Form backsplash Interior Door and Trim Standards White hollow core smooth painted interior doors, choose between 3 styles, 32" doors where applicable Colonial style wood base and door casing painted white finish Mortised hinges all doors Lever action passage and privacy locksets Colonial style wood casing and jamb with white finish all windows 2 ¼" mirror trim stained to match door/window trim color All interior decorative wood components added will match trim color **Floor Covering Standards** Carpet 14 oz ship loose not installed 5 lb rebond carpet pad ship loose Vinyl roll goods installed in the kitchen, baths, utility, and foyer per plan Interior Finish Standards Smooth wall finish painted white with hi-build primer Stipple finish ceiling painted white with hi-build primer Flush transition at ceiling line no beam Epoxy coated wire shelves closets & utility Closet organizer system in Bedroom 1 walk in closet. Per print **Appliances** Microwave prep over stove area No appliances standard Warrantv One year, 10 year structural as described on web page www.rochesterhomesinc.com (ID102006)

